

Professional CFM/CMM Thermo-Anemometer ET-950/955

The anemometer measures air velocity, air flow and temperature. It is designed for quality control, illness prevention & cure in various environments like constructional-engineering, factory, school, supermarket and household, etc.

FEATURES

- ◆ Wide range measurement
- ◆ Reading freezing
- ◆ Over-range indication
- ◆ Large backlit LCD display
- ◆ Max/Min measuring



Specifications

Function	Model	ET-950	ET-955
Circuit		Based on fast and high accurate MCU design	
Air Velocity Range		0.3~45.0 m/s; 59~8858 ft/min; 0.6~100.6 Mph;	1.0~162.0 km/s; 0.5~87.5 knots;
		N/A	0~9999×100 CMM 0~9999×100 CFM
Area Set		N/A	0.001~9999m ² (0.001~9999ft ²)
Temperature Range		-30~60°C(-22~140°F)	
Operation Conditions		0~60°C(32~140°F); <90% RH(Non-condensation)	
Storage Conditions		-40~60°C(14~140°F); < 80% RH	
Air Velocity Accuracy		3%±0.1	
Air Velocity Resolution		0.1m/s	
Sampling Time		1time/ second	
Temperature Accuracy		±1.5°C(±2.7°F)	
Air Velocity Level Indication		level 1-12 by analog bar-graph, level 12 above by digits	



Dimension(L*W*H): 185*66*33mm
Weight: 337g

Accessories: User's manual, 9V battery, tripod(optional), carrying case, large gift box